



# TYPE F AUTOMATIC TRANSMISSION FLUID

*Sinclair ATF Type F Fluid is a premium quality Ford approved fluid described by their specification M2C33-F. This fluid is recommended for all pre 1979 model Ford built automatic transmissions regardless of age. It is recommended for use in selected imported automatic transmissions or wherever a fluid meeting Ford's specification M2C33-F is required. It should not be used in any transmission calling for DEXRON® III, DEXRON® II, MERCON®, Ford fluids such as M2C166-H or M2C138-CJ Fluids. Sinclair ATF Type F Fluid is also approved for Detroit Diesel Allison C-3 applications.*



## APPLICATIONS

- All pre 1979 model and selected pre 1981 model Ford built transmissions.
- In selected imported automatic transmissions such as Ford Capri, Jaguar, Mazda, Saab 3-Speed, Triumph, Toyota (77-79), Toyota 4-Speed (79-83), and Volvo (77-85).
- Approved for Detroit Diesel Allison C-3 applications.
- Wherever a fluid meeting Ford's specification M2C33-F is required.
- May be used in some hydraulic and compressor systems where excellent low temperature flow ability is required.

## PERFORMANCE

Type F



# TYPE F AUTOMATIC TRANSMISSION FLUID

## TYPICAL PHYSICAL PROPERTIES

	METHOD	TYPICAL RESULTS
Viscosity Grade		Type F ATF
Gravity, °API	ASTM D287	32.6722
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8619
Viscosity @ 40°C cSt	ASTM D445	38.11
Viscosity @ 100°C cSt	ASTM D445	7.47
Viscosity Index	ASTM D2270	167
Brookfield Viscosity at -40°C, cP	ASTM D2983	37,000
Color	ASTM D1500	Red

Description	Pack Size	Part #	Each UPC	Case UPC	Case Dimensions	Case Cube / Pallet Cube	Case Weight / Pallet Weight	Pallet Stack
Type F ATF	6/1 Quart	525-006	0 14168-01613 1	0 14168-01773 2	L 9.500 x W 7.625 x H 9.625	0.403 / 68.194	12.360 / 1928.300	156 Cases (6 layers of 26)
Type F ATF	55 Gallon	525-003	0 14168-01686 5	N/A	L 23.000 x W 23.000 x H 35.000	10.715 / 44.444	425.886 / 1703.543	4 Drums

